

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME
(NICNAS)**

POLYMER OF LOW CONCERN PUBLIC REPORT

Polymer in ZK566026

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.
 Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
 TEL: + 61 2 8577 8800
 FAX: + 61 2 8577 8888
 Website: www.nicnas.gov.au

**Director
NICNAS**

May 2018

Table of Contents

SUMMARY	2
CONCLUSIONS AND REGULATORY OBLIGATIONS.....	2
ASSESSMENT DETAILS.....	4
1. APPLICANT AND NOTIFICATION DETAILS	4
2. IDENTITY OF POLYMER	4
3. PLC CRITERIA JUSTIFICATION	4
4. PHYSICAL AND CHEMICAL PROPERTIES.....	4
5. INTRODUCTION AND USE INFORMATION	4
6. HUMAN HEALTH RISK ASSESSMENT.....	5
7. ENVIRONMENTAL RISK ASSESSMENT	5
BIBLIOGRAPHY	6

SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1488	BASF Australia Ltd	Polymer in ZK566026	No	< 30 tonnes per annum	Component of automotive paint

CONCLUSIONS AND REGULATORY OBLIGATIONS

Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

Health and Safety Recommendations

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself. However, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

Disposal

- Where reuse or recycling are not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

Emergency Procedures

- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

Secondary Notification

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and*

Assessment) Act (1989) the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria;

or

- (2) Under Section 64(2) of the Act; if
 - the function or use of the notified polymer has changed from component of automotive paint, or is likely to change significantly;
 - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
 - the notified polymer has begun to be manufactured in Australia;
 - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

Safety Data Sheet

The SDS of products containing the notified polymer was provided by the applicant. The accuracy of the information on the SDS remains the responsibility of the applicant.

ASSESSMENT DETAILS

1. APPLICANT AND NOTIFICATION DETAILS

Applicants

BASF Australia Ltd (ABN: 62 008 437 867)
Level 12, 28 Freshwater Place
SOUTHBANK VIC 3006

Exempt Information (Section 75 of the Act)

Data items and details claimed exempt from publication: chemical name, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities and import volume.

2. IDENTITY OF POLYMER

Marketing Name

ZK566026 (product containing the notified polymer)

Molecular Weight

Number Average Molecular Weight (Mn) is > 10,000 g/mol

3. PLC CRITERIA JUSTIFICATION

<i>Criterion</i>	<i>Criterion met</i>
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa	Solid
Melting Point/Glass Transition Temperature	Not determined
Density	Not determined
Water Solubility	Dispersible
Dissociation Constant	Contains anionic functionalities and is likely to be ionised in the environmental pH range (4-9)
Particle Size	300 - 330 nm
Reactivity	Stable under normal environmental conditions
Degradation Products	None under normal conditions of use

5. INTRODUCTION AND USE INFORMATION

Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
Tonnes	< 30	< 30	< 30	< 30	< 30

Use

The notified polymer will not be manufactured in Australia. It will be imported as a component of finished paints at < 10% concentration. No further reformulation or repackaging will occur.

The paints containing the notified polymer at < 10% concentration will be used by professional painters at vehicle repair workshops. The paints will be applied by spray in a spray booth.

6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

Although not considered in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia.

The notified polymer is a high molecular weight (10,000-70,000 Da) polymer with low water solubility. Inhalation of polymers with molecular weights > 70,000 Da has been linked with irreversible lung damage due to lung overloading and impaired clearance of particles from the lung, particularly following repeated exposure (US EPA, 2017). While there is also a concern for polymers with molecular weights between 10,000 and 70,000 Da, it is acknowledged that there is a data gap for this range. Therefore, there is uncertainty for the potential for lung overloading effects with respect to the notified polymer. If the notified polymer is inhaled at low levels and/or infrequently, it is assumed that it will be cleared from the lungs. However, high level and/or frequent exposure may result in lung overloading effects, though the level of exposure in humans that would result in any effects, as well as the severity, is uncertain.

7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted by the notifier. Anionic polymers are generally of low toxicity to fish and daphnia, however they are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone, leading to chelation of essential nutrients. However, this does not apply to the notified polymer and it is therefore not considered to be an over-chelation hazard to algae (Boethling & Nabholz, 1997).

The notified polymer will not be manufactured in Australia. It will be imported as a component of finished industrial paints. These paints will be applied by spray by professional painters at vehicle repair workshops. As estimated by the notifier, about 30% of the import volume of the notified polymer could be released as overspray generated during use, and up to 5% of the import volume of the notified polymer could be released from cleaning of application equipment. However, most of this is expected to be collected and cured before disposed of to landfill in accordance with local government regulations. Release of the notified polymer to the environment in the event of accidental spills or leaks during storage, transport and use is expected to be absorbed on suitable materials and disposed of to landfill in accordance with local government regulations. Small amounts of the notified polymer may remain as residues in empty containers, which are also expected to be disposed of in accordance with local government regulations.

Following the application, the notified polymer is expected to share the fate of the articles on which it was applied, to be either recycled for metal reclamation or disposed of to landfill at the end of their useful life. During metal reclamation, the notified polymer will thermally decompose to form water vapour and oxides of carbon. In landfill, the notified polymer will be present as cured solids and will be neither bioavailable nor mobile. Thus, release of the notified polymer from the assessed use pattern

is not expected to lead to ecotoxicologically significant concentrations in the aquatic environment. The notified polymer is not expected to bioaccumulate based on its high molecular weight. The notified polymer in landfill is expected to eventually degrade via biotic and abiotic processes to form water and oxides of carbon.

Therefore, based on its assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the aquatic environment.

BIBLIOGRAPHY

Boethling, RS & Nabholz VJ (1997) Chapter 10 Environmental Assessment of Polymers under the U.S. Toxic Substances Control Act. In: Hamilton, JD Sutcliffe R ed. Ecological Assessment of Polymers Strategies for Product Stewardship and Regulatory Programs, 1st ed. New York, Van Nostrand Reinhold, pp 187-234

Safe Work Australia (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, <https://www.safeworkaustralia.gov.au/doc/model-code-practice-spray-painting-and-powder-coating>.