

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME  
(NICNAS)**

**POLYMER OF LOW CONCERN PUBLIC REPORT**

**Polymer in BYK-390**

This Assessment has been compiled in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (the Act) and Regulations. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS) is administered by the Australian Government Department of Health, and conducts the risk assessment for public health and occupational health and safety. The assessment of environmental risk is conducted by the Australian Government Department of the Environment and Energy.

This Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address: Level 7, 260 Elizabeth Street, SURRY HILLS NSW 2010, AUSTRALIA.  
 Postal Address: GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.  
 TEL: + 61 2 8577 8800  
 FAX: + 61 2 8577 8888  
 Website: [www.nicnas.gov.au](http://www.nicnas.gov.au)

**Director  
NICNAS**

June 2019

**Table of Contents**

SUMMARY .....	2
CONCLUSIONS AND REGULATORY OBLIGATIONS.....	2
ASSESSMENT DETAILS.....	4
1. APPLICANT AND NOTIFICATION DETAILS.....	4
2. IDENTITY OF POLYMER .....	4
3. PLC CRITERIA JUSTIFICATION .....	4
4. PHYSICAL AND CHEMICAL PROPERTIES.....	4
5. INTRODUCTION AND USE INFORMATION.....	4
6. HUMAN HEALTH RISK ASSESSMENT.....	5
7. ENVIRONMENTAL RISK ASSESSMENT .....	5
BIBLIOGRAPHY .....	6

## SUMMARY

The following details will be published in the NICNAS *Chemical Gazette*:

ASSESSMENT REFERENCE	APPLICANT(S)	CHEMICAL OR TRADE NAME	HAZARDOUS SUBSTANCE	INTRODUCTION VOLUME	USE
PLC/1541	Reschem Technologies Pty Ltd	Polymer in BYK-390	No	≤ 3 tonnes per annum	Component of industrial coatings

## CONCLUSIONS AND REGULATORY OBLIGATIONS

### Human Health Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the health of workers and the public.

### Environmental Risk Assessment

Based on the assumed low hazard and the assessed use pattern, the notified polymer is not considered to pose an unreasonable risk to the environment.

### Health and Safety Recommendations

- Water insoluble high molecular weight polymers have the potential to cause lung overloading. Respiratory protection and local exhaust ventilation should be used to prevent inhalation exposure if mist/dust/aerosol formation is expected.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- A copy of the SDS should be easily accessible to employees.
- Spray applications should be carried out in accordance with the Safe Work Australia Code of Practice for *Spray Painting and Powder Coating* (Safe Work Australia, 2015) or relevant State or Territory Code of Practice.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation should be in operation.

### Disposal

- Where reuse or recycling is not appropriate, dispose of the notified polymer in an environmentally sound manner in accordance with relevant Commonwealth, state, territory and local government legislation.

### Emergency Procedures

- Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.
- Spills and/or accidental release of the notified polymer should be handled by physical containment, collection and subsequent safe disposal.

**Secondary Notification**

This risk assessment is based on the information available at the time of notification. The Director may call for the reassessment of the polymer under secondary notification provisions based on changes in certain circumstances. Under Section 64 of the *Industrial Chemicals (Notification and Assessment) Act (1989)* the notifier, as well as any other importer or manufacturer of the notified polymer, have post-assessment regulatory obligations to notify NICNAS when any of these circumstances change. These obligations apply even when the notified polymer is listed on the Australian Inventory of Chemical Substances (AICS).

Therefore, the Director of NICNAS must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under Section 64(1) of the Act; if
  - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under Section 64(2) of the Act; if
  - the function or use of the notified polymer has changed from component of industrial coatings, or is likely to change significantly;
  - the amount of notified polymer being introduced has increased, or is likely to increase, significantly;
  - the notified polymer has begun to be manufactured in Australia;
  - additional information has become available to the person as to an adverse effect of the notified polymer on occupational health and safety, public health, or the environment.

The Director will then decide whether a reassessment (i.e. a secondary notification and assessment) is required.

**Safety Data Sheet**

The SDS of the product containing the notified polymer was provided by the applicant. The accuracy of the information on the SDS remains the responsibility of the applicant.

## ASSESSMENT DETAILS

### 1. APPLICANT AND NOTIFICATION DETAILS

#### Applicants

ResChem Technologies Pty Ltd (ABN: 90 315 656 219)  
Suite 1103, 4 Daydream St  
WARRIEWOOD NSW 2101

#### Exempt Information (Section 75 of the Act)

Data items and details exempt from publication include: chemical name, other names, CAS number, molecular and structural formulae, molecular weight, polymer constituents, residual monomers/impurities, and import volume.

### 2. IDENTITY OF POLYMER

#### Marketing Name(s)

BYK-390 (containing the notified polymer at  $\leq 50\%$  concentration)

#### Molecular Weight

Number Average Molecular Weight (Mn) is  $> 10,000$  g/mol

### 3. PLC CRITERIA JUSTIFICATION

<i>Criterion</i>	<i>Criterion met</i>
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

### 4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20 °C and 101.3 kPa	Light yellow liquid*
Melting Point/Glass Transition Temperature	295 °C <sup>^</sup>
Density	$> 900$ kg/m <sup>3</sup> at 20 °C*
Water Solubility	Immiscible*
Dissociation Constant	Contains no dissociable functionality
Reactivity	Stable under normal environmental conditions
Degradation Products	None under normal conditions of use
* For BYK-390 (formulation containing the notified polymer at $\leq 50\%$ concentration)	
<sup>^</sup> Estimated using EPI Suite	

### 5. INTRODUCTION AND USE INFORMATION

#### Maximum Introduction Volume of Notified Chemical (100%) Over Next 5 Years

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
Tonnes	0 – 3	0 – 3	0 – 3	0 – 3	0 – 3

## Use

The notified polymer will be used as a component of industrial coatings.

The notified polymer will not be manufactured in Australia. It will be imported at  $\leq 50\%$  concentration for local reformulation. The reformulation process would involve mixing the notified polymer with other coating additives, and pouring the finished coating into spray guns or paint trays prior to application. Workers are expected to wear appropriate PPE, including goggles, gloves, protective clothing and respiratory protection if necessary.

Finished coatings containing the notified polymer at  $\sim 0.25\%$  will be only available to professional workers. The coatings will be applied by brush, roller or spray. Once the coatings are cured, the notified polymer will be bound into an inert film and will not be available for exposure.

## 6. HUMAN HEALTH RISK ASSESSMENT

No toxicological data were submitted. The notified polymer meets the PLC criteria and is therefore assumed to be of low hazard. The risk of the notified polymer to occupational and public health is not considered to be unreasonable given the assumed low hazard and the assessed use pattern.

It is noted that the notified polymer is water-insoluble with molecule weight  $> 10,000$  g/mol. Inhalation of polymers with molecular weights  $> 70,000$  g/mol has been linked with irreversible lung damage due to lung overloading and impaired clearance of particles from the lung, particularly following repeated exposure (US EPA, 2019). There is a data gap for polymers with MW between 10,000 and 70,000 g/mol, and uncertainty may exist. If the notified polymer is inhaled at low levels and/or infrequently, it is assumed that it will be cleared from the lungs.

Although not considered in this risk assessment, NICNAS notes that the notified polymer contains residual monomers that are classified as hazardous according to the *Globally Harmonised System of Classification and Labelling of Chemicals (GHS)*, as adopted for industrial chemicals in Australia.

## 7. ENVIRONMENTAL RISK ASSESSMENT

No ecotoxicological data were submitted. Polymers without significant ionic functionality are generally of low concern to the environment.

The notified polymer will not be manufactured in Australia. It will be imported as the formulation BYK-390, used as a surface additive for reformulation into industrial coating mixtures. Release of the notified polymer to the environment in the event of accidental spills or leaks during storage, transport and use is expected to be absorbed on suitable materials and disposed of to landfill in accordance with local government regulations. The coatings will be applied by professional applicators in industrial settings. The formulated product may be applied by spray techniques (40%), brush (10%) or roller (50%). As estimated by the notifier, about 20-30% of the product could be released as overspray generated during use. The overspray is expected to be collected on kraft paper or newspaper in spray booths before disposal to landfill in accordance with local government regulations. The notifier estimates that approximately 1% of the total import volume will be lost due through spillages. Under a worst case scenario, the notifier estimates that 1% of the notified polymer as liquid waste from application equipment cleaning could be washed into sewers. Assuming that none of the notified polymer will be removed via absorption to sludge in the sewage treatment plant, the resultant predicted environmental concentration (PEC) in sewage effluent on a nationwide basis is estimated as  $0.02 \mu\text{g/L}$  [ $\text{PEC}_{\text{river}} = 0.08 \text{ kg notified polymer/day} \div (200 \text{ L/person/day} \times 24.386 \text{ million people}) \times 1$  (dilution factor)]. However, the notified polymer is insoluble in water and is not expected to hydrolyse or ionise in the environmental pH range (4–9). The notified polymer is not expected to cross biological membranes due to its high molecular weight and low water solubility and is therefore not expected to bioaccumulate.

Following the application, most of the notified polymer is expected to share the fate of the article to which it has been applied, either subjected to metal reclamation processes or disposed of to landfill at the end of its useful life. During metal reclamation processes, the notified polymer will thermally decompose to form water vapour and oxides of carbon. In landfill, the notified polymer will be present as cured solids and will be neither bioavailable nor mobile. Thus, release of the notified polymer from the assessed use pattern is not expected to lead to ecotoxicologically significant concentrations in the aquatic environment. In landfill, the notified polymer is expected to eventually degrade via biotic and abiotic processes to form water and oxides of carbon.

Therefore, based on its assumed low hazard, the notified polymer is not considered to pose an unreasonable risk to the environment.

### **BIBLIOGRAPHY**

Safe Work Australia (2015) Code of Practice: Spray Painting and Powder Coating, Safe Work Australia, <https://www.safeworkaustralia.gov.au/doc/model-code-practice-spray-painting-and-powder-coating>.

US EPA (2019) <https://www.epa.gov/reviewing-new-chemicals-under-toxic-substances-control-act-tsca/high-molecular-weight-polymers-new>, accessed on April 2019