

File No SAPLC/49

12 July 2006

**NATIONAL INDUSTRIAL CHEMICALS NOTIFICATION AND ASSESSMENT SCHEME
(NICNAS)**

FULL PUBLIC REPORT

Polymer in JONCRYL LMV 7085

This Self Assessment has been compiled by the applicant and adopted by NICNAS in accordance with the provisions of the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth) (the Act) and Regulations. This legislation is an Act of the Commonwealth of Australia. The National Industrial Chemicals Notification and Assessment Scheme (NICNAS), administered by the Department of Health and Ageing and the Department of the Environment and Heritage has screened this assessment report. The data supporting this assessment will be subject to audit by NICNAS.

For the purposes of subsection 78(1) of the Act, this Full Public Report may be inspected at:

Library
Australian Safety and Compensation Council
25 Constitution Avenue
CANBERRA ACT 2600
AUSTRALIA

To arrange an appointment contact the Librarian on TEL + 61 2 6279 1162 or email ascc.library@dewr.gov.au

This Full Public Report is available for viewing and downloading from the NICNAS website or available on request, free of charge, by contacting NICNAS. For requests and enquiries please contact the NICNAS Administration Coordinator at:

Street Address:	334 - 336 Illawarra Road MARRICKVILLE NSW 2204, AUSTRALIA.
Postal Address:	GPO Box 58, SYDNEY NSW 2001, AUSTRALIA.
TEL:	+ 61 2 8577 8800
FAX	+ 61 2 8577 8888.
Website:	www.nicnas.gov.au

**Director
NICNAS**

TABLE OF CONTENTS

FULL PUBLIC REPORT.....	3
1. APPLICANT AND NOTIFICATION DETAILS	3
2. IDENTITY OF CHEMICAL	3
3. PLC CRITERIA JUSTIFICATION	3
4. PHYSICAL AND CHEMICAL PROPERTIES	4
5. INTRODUCTION AND USE INFORMATION.....	4
6. HUMAN HEALTH IMPLICATIONS.....	5
6.1. Exposure Assessment	5
6.2. Toxicological Hazard Characterisation	5
6.3. Human Health Risk Assessment.....	5
7. ENVIRONMENTAL IMPLICATIONS	5
7.1. Exposure Assessment	5
7.2. Environmental Hazard Characterisation	6
7.3. Environmental Risk Assessment	6
8. CONCLUSIONS.....	6
8.1. Level of Concern for Occupational Health and Safety	6
8.2. Level of Concern for Public Health.....	6
8.3. Level of Concern for the Environment	6
9. MATERIAL SAFETY DATA SHEET.....	6
9.1. Material Safety Data Sheet	6
10. RECOMMENDATIONS	6
10.1. Secondary Notification	7

FULL PUBLIC REPORT**Polymer in JONCRYL LMV 7085****1. APPLICANT AND NOTIFICATION DETAILS**

APPLICANT(S)

JohnsonDiversey Australia Pty Ltd
29 Chifley Street
SMITHFIELD NSW 2164 Australia
ABN 90 000 065 725

NOTIFICATION CATEGORY

Self Assessment: Polymer of Low Concern

EXEMPT INFORMATION (SECTION 75 OF THE ACT)

Data items and details claimed exempt from publication:
Chemical Name, Other Names, CAS Number, Molecular and Structural Formulae, Molecular Weight,
Polymer Constituents, Residual Monomers/Impurities, Use Details

PREVIOUS NOTIFICATION IN AUSTRALIA BY APPLICANT(S)

None

NOTIFICATION IN OTHER COUNTRIES

This polymer has been notified on the Canadian DSL NSN 12696 added 12/21/2003 to DSL, US TSCA PMN P-03-379 confidential TSCA. Acc# 137736 and Korean KECL inventories KE# 2004-3-2980 by Johnson Polymer, LLC a division of JohnsonDiversey Inc.

2. IDENTITY OF CHEMICAL

MARKETING NAME(S)

Polymer in JONCRYL LMV 7085

MOLECULAR WEIGHT (MW)

Number Average Molecular Weight (Mn) >1000

REACTIVE FUNCTIONAL GROUPS

The notified polymer contains only low concern functional groups.

3. PLC CRITERIA JUSTIFICATION

<i>Criterion</i>	<i>Criterion met (yes/no/not applicable)</i>
Molecular Weight Requirements	Yes
Functional Group Equivalent Weight (FGEW) Requirements	Yes
Low Charge Density	Yes
Approved Elements Only	Yes
Stable Under Normal Conditions of Use	Yes
Not Water Absorbing	Yes
Not a Hazard Substance or Dangerous Good	Yes

The notified polymer meets the PLC criteria.

4. PHYSICAL AND CHEMICAL PROPERTIES

Appearance at 20°C and 101.3 kPa	Clear, slightly yellow liquid (Product JONCRYL LMV 7085) – White powdery substance when freeze dried
Melting Point/Glass Transition Temp	Tg: 77°C
Density	1090 kg/m ³ at 25°C (product JONCRYL® LMV 7085)
Water Solubility	soluble in water at pH 2 – 380 mg/L (10g sample) Miscible in water at pH 7 and pH 9 – 100% soluble in water (All material in solution)
Dissociation Constant	pKa = 4.88 (estimated to be similar to propionic acid)
Particle Size	Not applicable (liquid)
Reactivity	Contains hydrolysable groups but is likely to be stable under normal environmental conditions (pH 4-9)
Degradation Products	None under normal conditions of use. Slowly degrades into oxides of carbon and water.

Comments

Water solubility and hydrolytic stability tests were conducted on this polymer according to OECD protocols 120 and 111, respectively. It showed that the substance is soluble at pH 2 and miscible in water at pH 7 and 9. However, this polymer was found to be very hydrolytically stable at pH 4 – 7 – 9 at 50°C. JONCRYL® LMV 7085 is a solution of an anionic polymer in water at neutral conditions. The Tg of this polymer was tested using Differential Scanning Calorimetry (DSC). Test temperature range: 25°C to 150°C at 15°C/min
Density of the polymer was measured using a Pycnometer method (Weight/Volume).

5. INTRODUCTION AND USE INFORMATION

MAXIMUM INTRODUCTION VOLUME OF NOTIFIED CHEMICAL (100%) OVER NEXT 5 YEARS

<i>Year</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>
<i>Tonnes</i>	15-20	20-25	25-30	30-35	35-40

USE AND MODE OF INTRODUCTION AND DISPOSAL

Mode of Introduction

The notified polymer will be imported into Australia in a 35% water based polymer resin solution contained in a 220kg closed head plastic drum. It will be transported from the port to a warehouse by truck. It will be transported from the warehouse, by truck, to a customer site where it will be formulated into ink.

Reformulation/manufacture processes

During formulation, the notified polymer will be weighed and then transferred to an ink mixing vessel. Once combined with other ingredients, it will be filled into 1-5 L or 200 kg plastic containers. The notified polymer comprises 12 wt. % or less of the wet ink formulation.

Use

Binder for printing inks used for corrugated boxes. The polymer acts as a binder between the dyes and the substrate. The packaged containers are shipped to a printing company who will apply the ink to paper used in the manufacture of corrugated boxes. The ink will be applied using standard printing methods using automated printing press machine.

6. HUMAN HEALTH IMPLICATIONS

6.1. Exposure Assessment

OCCUPATIONAL EXPOSURE

While transporting and warehousing this polymer, it is unlikely that workers will come into dermal or ocular contact with the notified polymer. During ink formulation, workers will manually weigh and transfer the polymer to a mixing vessel. Workers are expected to wear impermeable gloves, eye protection and protective clothing. During the final application of the ink onto the paper, workers are also expected to wear protective gear. Once the ink has dried, the polymer becomes part of a dried coating and exposure is limited.

PUBLIC EXPOSURE

The notified polymer will not be available to the public. The public will come into contact with the notified polymer once the ink dries on a cardboard box. At this point the polymer is not readily available for exposure.

6.2. Toxicological Hazard Characterisation

No toxicological data were submitted. The notified polymer meets the PLC criteria and can therefore be considered to be of low hazard.

6.3. Human Health Risk Assessment

OCCUPATIONAL HEALTH AND SAFETY

The OHS risk presented by the notified polymer is low based on the low hazard and low exposure. In addition, the personal protective equipment and engineering controls further limit exposure during the handling of the product containing the notified substance.

PUBLIC HEALTH

The notified polymer is not sold to the public and is only used by industrial ink formulators and printing press operators. Once the polymer is applied and dried, it becomes part of the paper container and hence is not bioavailable. Therefore, the risk to the public is considered very low.

7. ENVIRONMENTAL IMPLICATIONS

7.1. Exposure Assessment

ENVIRONMENTAL RELEASE

No aquatic environment exposure is expected during the import of the notified polymer; the polymer will be imported in a closed head plastic drum and sold to an ink manufacturer.

A small amount (<1%) of the notified polymer may be released during reformulation, due to spills and cleaning of equipment, a further small amount (<1%) could be washed off from printing machinery during the normal cleaning process. An organic solvent will be used for cleaning and a licensed disposal contractor for off-site solvent regeneration will deal with this, with the notified polymer being disposed of to landfill.

Residues remaining in the import containers (1-2%) will be disposed of either through metal recycling companies or the controlled waste system (plastic cans) and be disposed of by incineration or washed and sent to landfill.

During recycling of cardboard products, some of the notified polymer is likely to be dissolved or dispersed in water. A portion of this will absorb to the sludge in the sewage treatment plant (STP), with the remainder being released to the aquatic environment.

The majority of the notified polymer will be bound within the cured coating matrix adhering to printing inks, varnishes and self-adhesive labels. Once the chemical is within a cured coating it is likely to share the fate of the substrate, which might involve recycling or landfill.

ENVIRONMENTAL FATE

The notified polymer is relatively water soluble, expected to be hydrolytically stable and not expected to be readily biodegradable. On the basis of water solubility, the notified polymer is likely to be mobile in soils, and should work its way into the grass root zone and below. The polymer should not hydrolyse (no functional groups are expected to hydrolyse in the environmental pH range of 4 – 9), but is expected to slowly degrade to oxides of carbon and water. Incineration of the notified polymer will result in the generation of water vapour and carbon dioxide. The notified polymer's high molecular weight will preclude absorption across biological membranes and thus it is unlikely to bioaccumulate.

7.2. Environmental Hazard Characterisation

Anionic polymers are known to be moderately toxic to algae. The mode of toxic action is over-chelation of nutrient elements needed by algae for growth. The highest toxicity is when the acid is on alternating carbons of the polymer backbone. This could apply to the notified polymer. However, the toxicity to algae is likely to be further reduced due to the presence of calcium ions, which will bind to the functional groups.

7.3. Environmental Risk Assessment

The notified polymer will be used as a component of inks. Once these inks have been cured the notified polymer is expected to remain within the product matrices. Hence, the majority of the notified polymer will share the fate of the articles into which it is incorporated. It is anticipated that these will be disposed of to landfill, incinerated or recycled at the end of their useful lifetime. In landfill it is expected that the notified polymer will remain immobile within the soil. During recycling of cardboard products, some of the notified polymer is likely to be dissolved or dispersed in water. A portion of this will absorb to the sludge in the (STP), with the remainder being released to the aquatic environment. Incineration of the notified polymer will result in the formation of water vapour and oxides of carbon and nitrogen.

The above considerations indicate minimal risk to the environment when the notified polymer is used in the proposed manner.

8. CONCLUSIONS

8.1. Level of Concern for Occupational Health and Safety

There is Low Concern to occupational health and safety under the conditions of the occupational settings described.

8.2. Level of Concern for Public Health

There is Negligible Concern to public health when used in the proposed manner.

8.3. Level of Concern for the Environment

The polymer is not considered to pose a risk to the environment based on its reported use pattern.

9. MATERIAL SAFETY DATA SHEET

9.1. Material Safety Data Sheet

The notifier has provided MSDS as part of the notification statement. The accuracy of the information on the MSDS remains the responsibility of the applicant.

10. RECOMMENDATIONS

CONTROL MEASURES

Occupational Health and Safety

- No specific engineering controls, work practices or personal protective equipment are required for the safe use of the notified polymer itself, however, these should be selected on the basis of all ingredients in the formulation.

Guidance in selection of personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

- Printing workers should wear disposable gloves and ensure adequate ventilation is present when handling containers with ink containing the notified polymer and during routine maintenance and repairs of the printing machinery.
- A copy of the MSDS should be easily accessible to employees.
- If products and mixtures containing the notified polymer are classified as hazardous to health in accordance with the NOHSC *Approved Criteria for Classifying Hazardous Substances*, workplace practices and control procedures consistent with provisions of State and Territory hazardous substances legislation must be in operation.

Disposal

- The notified polymer should be disposed of to landfill or incineration
- Empty containers should be sent to local recycling or waste disposal facility

Emergency procedures

- Accidental, spills/release of the notified polymer should be handled by absorption with sand and putting into a suitable container for disposal. Contaminated containers can be re-used after cleaning

10.1. Secondary Notification

The Director of Chemicals Notification and Assessment must be notified in writing within 28 days by the notifier, other importer or manufacturer:

- (1) Under subsection 64(1) of the Act; if
 - the notified polymer is introduced in a chemical form that does not meet the PLC criteria.

or

- (2) Under subsection 64(2) of the Act:
 - if any of the circumstances listed in the subsection arise.

The Director will then decide whether secondary notification is required.